




**SPECTRA Polaris
Print Head 35pl**



Main Features:



Carriage



Dual thermal drying fans



Home position



**Ink supply system
with cobetter® filter**

★ High resolution, high speed

8 pieces of SPECTRA Polaris PQ 512 hi-speed and hi-res durable print heads
High speed up to 210 m²/h
Double silent linear guide on expanded horizontal beam
Robust body structure perfectly supports high speed

★ New innovation

Constant tensioned taking up /feeding system ensures long precise feeding.
Rigid CNC milled aluminum block print head mounting base
Chamfered print head mounting base avoids media scratch
New improved CNC milled aluminum capping seals print head tightly

★ Multifunction

Roll to roll media feeding system.
8 print heads in 2 offset rows ensures high production.
New high frequency control boards protect print head and enable hi-speed.

★ Easy control

Photoprint 10 /Maintop...+GZ control console.
USB 2.0 for large volumes of data transferring.
LED light provides convenient working environment.



PLR-35(II) Ink



Photoprint 10



Dual silent linear guide and LED light

T3208AU

ITEM		SPECIFICATIONS
Tech.	Model	StormJet T3208AU
	Print head	8 SPECTRA Polaris PQ 512 35pl/15pl
	Technology	Drop-on-Demand Piezo inkjet technology
	Output resolution	X:300dpi /600dpi Y:400dpi /600dpi /800dpi
	Media clearance	1mm-18mm adjustable head height
Ink	Outdoor durability	1 year outdoor life /2 years (optional)
	Solvent ink	C.M.Y.K
	Ink supply	Bulk ink supply system with cobetter® filter
Drying system	Heating system	Pre, mid and post heaters controlled by PID
	Temp. range	Adjustable up to 80℃, recommend temp. 40℃-50℃
	Drying system	Dual thermal drying fans+ extended heater
Media	Print width	Max:3200mm
	Media type	Banner, PP, Adhesive, Vinyl, Film...
	Transportation	Auto feeder+ auto taking-up system by infrared sensor
Printing speed and mode		300×400 dpi 2pass 210m²/h
		300×600 dpi 3pass 155m²/h
		300×800 dpi 4pass 110m²/h
Other	Interface	USB 2.0
	Environment	Temp.:23℃-29℃, Humidity: 50%-80%
	Software	Photoprint 10 /Maintop...+GZ control console
	Power	50Hz /AC220V(±10%) 15(printer)+16Ax2(thermal fans)
	Dimension	LxWxH (mm): 5100x1000x1500

Specifications are liable to change without prior notice. All trademarks mentioned are property of their respective owners.



Company info:

Gongzheng Group Co., Ltd.

Add: Five-Star Industrial Zone, Oubei Town, Yongjia County, Zhejiang Province, China 325105

Tel: +86 577 6731 9778

Fax: +86 577 6731 9775

Email: gzsales@gongzheng.com

Web: www.gongzheng.com

