

SFB-10 Front-Lit



***Merry
Christmas!***
& Happy Newyear!

Starflex, The Professionals' partner

manufactured by **Starflex**

Features & Applications

- Width : 80cm (31") ~ 220cm(87"), 320cm(125") ~ 530cm(210") seamless
- White opaque substrate for front-lit display
- Soft and delicate surface
- Various choice of color - white, snow white, yellow, red, green, blue, black and etc
- Banners and in-store display • Matt & glossy available • Weather resistant
- Printable with Vutek, Scitex, Nur, Mimaki, Roland, Mutoh, Jeti, Seiko and etc.

Specification

(250Dx500D, 18x12)

Properties	Test Method	Unit	Result
Transmittance	ASTM E 424 6.5.2	%	13.7
Tensile Strength	ISO 13934-1:1999 C.R.E.CUT STRIP METHOD	KGF/5CM	L : 90.1 W : 89.3
Tearing Strength	ISO 13937-2:2000 C.R.E.SINGLE TEAR METHOD	KGF	L : 7.1 W : 5.0
Elongation	ISO 13934-2:2000 C.R.E.CUT STRIP METHOD	%	L : 14.9 W : 31.2
Adhesion Strength	ISO 2411.C.R.E	KGF/5CM	13.2
Flexing Endurance at Low Temp.	DIN53351	CYCLES	17000
Resistance to Low Temp.	DIN53351		-20℃
Resistance to High Temp.	DIN53351		80℃
Resistance to Weathering	ASTM G26, XENON ARCLAMP, 18MIN SPRAY/2HRS., 100HRS. EXPOSURE		NO CHANGE
Practice for operating light-exp. With and without water	ASTM G26, METHOD A, TYPE B, WEATHER-O-METER	GRADE	4