

R03C RGB Domestic LED 5050PKG 0.72W



Shape	Cover type	Power Dissipation	0.72W
Color	RGB	View angle	120 degrees

DETAIL VIEW

- Excellent Waterproof of IP68
- Maintenance 70% of Longtime Life Illumination
- Luxury Appearance by ABS Molding Injection
- Excellent Stability
- Very Easy Installation

APPLICATION

Signage, Channel letter, Architecture, Indoor&Outdoor Lighting etc...

SPECIFICATION

Product	R03C RGB Domestic LED 5050PKG 0.72W
LED CHIP PKG	Domestic 5050 PKG
Operating Power	DC12V
Power/Current Dissipation	0.72W 60mA
LED Spec	120° view angle, 50,000hr rated life, made in korea
Luminous intensity(mcd)	R(1,800)G(3,900)B(1,200)
Dominent wavelength	R(625)G(525)B(460)
Module connection & cuttability	wire to wire series connection, every module
Recommended channel height	Min. 80mm
Dimension	15mm(W)*71mm(L)*8mm(H)
Wire length	90mm
Piece weight	9.9 g
Operating temperature	-20°C~60°C
Storage temperature	-30°C~70°C
Waterproof rate	IP68
Cable	AWG18
Case materials	ABS housing
working hours	50,000hr